



TOPBiHiKu7

N-type Bifacial TOPCon Technology

690 W ~ 720 W

CS7N-690 | 695 | 700 | 705 | 710 | 715 | 720TB-AG

MORE POWER



Module power up to 720 W
Module efficiency up to 23.2 %



Up to 85% Power Bifaciality,
more power from the back side



Excellent anti-LeTID & anti-PID performance.
Low power degradation, high energy yield



Lower temperature coefficient (Pmax): -0.29%/°C,
increases energy yield in hot climate



Lower LCOE & system cost

MORE RELIABLE



Tested up to ice ball of 35 mm diameter
according to IEC 61215 standard



Minimizes micro-crack impacts



Heavy snow load up to 5400 Pa,
wind load up to 2400 Pa*

12
Years

**Enhanced Product Warranty on Materials
and Workmanship***

30
Years

Linear Power Performance Warranty*

**1st year power degradation no more than 1%
Subsequent annual power degradation no more than 0.4%**

*According to the applicable Canadian Solar Limited Warranty Statement.

MANAGEMENT SYSTEM CERTIFICATES*

ISO 9001: 2015 / Quality management system ISO 14001: 2015 / Standards
for environmental management system ISO 45001: 2018 / International
standards for occupational health & safety IEC 62941: 2019 / Photovoltaic
module manufacturing quality system

PRODUCT CERTIFICATES*

IEC 61215 / IEC 61730 / CE / INMETRO / MCS / UKCA / CGC
CEC listed (US California) / FSEC (US Florida)
UL 61730 / IEC 61701 / IEC 62716 / IEC 60068-2-68
UNI 9177 Reaction to Fire: Class 1 / Take-e-way



* The specific certificates applicable to different module types and markets will vary,
and therefore not all of the certifications listed herein will simultaneously apply to the
products you order or use. Please contact your local Canadian Solar sales representative
to confirm the specific certificates available for your Product and applicable in the regions
in which the products will be used.



CSI Solar Co., Ltd. is committed to providing high quality solar
photovoltaic modules, solar energy and battery storage solutions
to customers. The company was recognized as the No. 1 module
supplier for quality and performance/price ratio in the IHS Module
Customer Insight Survey. Over the past 23 years, it has successfully
delivered over 125 GW of premium-quality solar modules across
the world.

* For detailed information, please refer to the Installation Manual.


CSI Solar Co., Ltd.

199 Lushan Road, SND, Suzhou, Jiangsu, China, 215129, www.csisolar.com, support@csisolar.com

Rear View



A



		Nominal Max. Power (Pmax)	Opt. Operating Voltage (Vmp)	Opt. Operating Current (Imp)	Open Circuit Voltage (Voc)	Short Circuit Current (Isc)	Module Efficiency
CS7N-690TB-AG690 W			39.6 V	17.43 A	47.5 V	18.39 A	22.2%
Bifacial Gain**	5%	725 W	39.6 V	18.30 A	47.5 V	19.31 A	23.3%
	10%	759 W	39.6 V	19.17 A	47.5 V	20.23 A	24.4%
	20%	828 W	39.6 V	20.92 A	47.5 V	22.07 A	26.7%
CS7N-695TB-AG695 W			39.8 V	17.47 A	47.7 V	18.44 A	22.4%
Bifacial Gain**	5%	730 W	39.8 V	18.34 A	47.7 V	19.36 A	23.5%
	10%	765 W	39.8 V	20.96 A	47.7 V	22.13 A	26.8%
	20%	834 W	40.0 V	17.51 A	47.9 V	18.49 A	22.5%
CS7N-700TB-AG700 W			40.0 V	18.39 A	47.9 V	19.41 A	23.7%
Bifacial Gain**	5%	735 W	40.0 V	19.26 A	47.9 V	20.34 A	24.8%
	10%	770 W	40.2 V	17.55 A	48.1 V	18.54 A	22.7%
	20%	840 W	40.2 V	18.43 A	48.1 V	19.47 A	23.8%
CS7N-705TB-AG705 W			40.2 V	21.06 A	48.1 V	22.25 A	27.2%
Bifacial Gain**	5%	740 W	40.4 V	17.59 A	48.3 V	18.59 A	22.9%
	10%	776 W	40.4 V	18.45 A	48.3 V	19.52 A	24.0%
	20%	846 W	40.4 V	21.11 A	48.3 V	22.31 A	27.4%
CS7N-710TB-AG710 W			40.6 V	17.63 A	48.5 V	18.64 A	23.0%
Bifacial Gain**	5%	746 W	40.6 V	18.51 A	48.5 V	19.57 A	24.2%
	10%	782 W	40.6 V	19.39 A	48.5 V	20.50 A	25.3%
	20%	852 W	40.6 V	21.16 A	48.5 V	22.37 A	27.6%
CS7N-715TB-AG715 W			40.8 V	17.67 A	48.7 V	18.69 A	23.2%
Bifacial Gain**	5%	751 W	40.8 V	18.55 A	48.7 V	19.62 A	24.3%
	10%	787 W	40.8 V	19.44 A	48.7 V	20.56 A	25.5%
	20%	858 W	40.8 V	21.20 A	48.7 V	22.43 A	27.8%
CS7N-720TB-AG720 W							
Bifacial Gain**	5%	756 W					
	10%	792 W					
	20%	864 W					

** Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

Operating Temperature	-40°C ~ +85°C
Max. System Voltage	1500 V (IEC/UL)
Module Fire Performance	TYPE 29 (UL 61730) or CLASS C (IEC61730)
Max. Series Fuse Rating	35 A
Protection Class	Class II
Power Tolerance	0 ~ + 10 W
Power Bifaciality*	80 %

* The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. CSI Solar Co., Ltd. reserves the right to make necessary adjustment to the information described herein at any time without further notice.

Please be kindly advised that PV modules should be handled and installed by qualified people who have professional skills and please carefully read the safety and installation instructions before using our PV modules.

	Nominal Max. Power (Pmax)	Opt. Operating Voltage (Vmp)	Opt. Ope- rating Current (Imp)	Open Circuit Voltage (Voc)	Short Circuit Current (Isc)
CS7N-690TB-AG522 W		37.4 V	13.94 A	45.0 V	14.83 A
CS7N-695TB-AG526 W		37.6 V	13.97 A	45.2 V	14.87 A
CS7N-700TB-AG529 W		37.8 V	14.00 A	45.4 V	14.91 A
CS7N-705TB-AG533 W		38.0 V	14.03 A	45.5 V	14.95 A
CS7N-710TB-AG537 W		38.2 V	14.06 A	45.7 V	14.99 A
CS7N-715TB-AG541 W		38.4 V	14.09 A	45.9 V	15.03 A
CS7N-720TB-AG544 W		38.6 V	14.12 A	46.1 V	15.07 A

MECHANICAL DATA

Specification	Data
Cell Type	TOPCon cells
Cell Arrangement	132 (2x (11x6))
Dimensions	2384 × 1303 × 33 mm (93.9 × 51.3 × 1.30 in)
Weight	37.8 kg (83.3 lbs)
Front Glass	2.0 mm heat strengthened glass with anti-reflective coating
Back Glass	2.0 mm heat strengthened glass
Frame	Anodized aluminium alloy
J-Box	IP68, 3 bypass diodes
Cable	4.0 mm ² (IEC), 12 AWG (UL)
Cable Length	360 mm (14.2 in) (+) / 200 mm (7.9 in) (-) or

(Including Connector)customized length*

Connector	T6 or MC4-EVO2 or MC4-EVO2A
Per Pallet	33 pieces
Per Container (40' HQ)	594 pieces or 495 pieces (only for US & Canada)

* For detailed information, please contact your local Canadian Solar sales and technical representatives.

TEMPERATURE CHARACTERISTICS

Specification	Data
Temperature Coefficient (Pmax)	-0.29 % / °C
Temperature Coefficient (Voc)	-0.25 % / °C
Temperature Coefficient (Isc)	0.05 % / °C
Nominal Module Operating Temperature	41 ± 3°C

PARTNER SECTION

